

→

/

→

C


:
 18V DC~32V DC (24V DC)
 85V AC~265V AC (120V DC~360V DC)
 (2 5):
 0~60V AC; 0~110V AC; 0~220V AC
 0~380V AC; 0~600V AC; 0~1000V AC

 (7 8 9):
 4mA~20mA
 0(4)mA~20mA; 0mA~10mA
 1~5V; 0~5V; 0~10V
 :
 $R_L \leq [(U-3)/0.022] \Omega$; U
 0(4)mA~20mA $\leq 550 \Omega$; 0mA~10mA $\leq 1.1k \Omega$
 0(1)~5V $\geq 1M \Omega$; 0~10V $\geq 2M \Omega$

 : 0.2%F.S. (0~110%)
 : < 5mV_{rms} (250 Ω)
 : 0.01%F.S./ $^{\circ}C$
 : 40Hz~1kHz
 : < 500ms
 : 2
 : EMC IEC 61326-3-1
 (1mA 1):
 1500 V AC(/ /)
 :
 -20 $^{\circ}C$ ~+60 $^{\circ}C$
 10%RH~90%RH(40 $^{\circ}C$)
 80kPa~106kPa
 -40 $^{\circ}C$ ~+80 $^{\circ}C$
 :
 24V DC供电 < 1W
 220V AC供电 < 2W

Nanjing New Power Electric Co., Ltd.





-
-
-

A

DIN

-
- PWR ()
- ALM ()

B

-
-
-
-
-
-
-

IEC/EN 60664-1 2

IEC 61000-4

C

-
-